

8"-10" CAPACITY COMPARISON

Manufacturer	Salsco	Salsco	Salsco	Wallenstein	Bear Cat	Bear Cat	Brush Bandit	Brush Bandit
Model	6210PTO	6210XT	810PTO	BX92S	CH8540	CHF9540H	95	90XP
Capacity	10" Rd. wood cap. (max 14" slab)	10" Rd. wood cap. (max 14" slab)	10" Rd. wood cap. (max 18" slab)	10"	8"	9"	9"	9"
HP Requirements	PTO Driven, 35 HP minimum required at the PTO. Gravity Feed	PTO Driven, 35HP minimum required at the PTO. Hydraulic Feed	PTO Driven, 35HP minimum required at the PTO. Hydraulic Feed (self contained hydraulics)	PTO Driven, 85HP to 110HP	PTO Driven, 35HP to 60HP required, Gravity Feed	PTO Driven, 35HP TO 60HP required	PTO Driven Range 230 HP - 60 HP	PTO Driven Range 30HP to 60 HP
Infeed Opening	10"H X 14"W	10"H X 14"W	10"H X 18"W	10" X 15"	9" X 9"	9" x 9"	9" x 17"	9 1/2" X 17"
Impeller Housing	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	1/4" thick steel wrap. Impeller housing is vented to provide more air flow for chip exhaust.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available
Impeller	1" thick X 42" dia. Fully balanced, 3 exhaust paddles welded & gusseted. 410 lbs.	1" thick X 42" dia. Fully balanced, 3 exhaust paddles welded & gusseted. 410 lbs.	2" thick x 32" dia. Fully balanced, 6 exhaust paddles welded & gusseted. 600 lbs.	36" 280 LBS.	30" x 1"inch thick, 275 LBS.	30" x 1"inch thick, 275 LBS.	34" dia. X 1" thick	30" dia. X 1 1/2" thick
Chipper Knives	(9) 1/2" thick x 4" long, double sided.	(9) 1/2" thick x 4" long, double sided.	(4) 1/2" thick x 7" long, double sided.	4 knives	4 reversible chipper blades	16 smaller double sided blades	9/16" thick X3 5/8" reversible	1/2" thick X 4" X 5 1/8" reversible
Bed Knives	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel.	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel.	(2) One horizontal and one vertical. Replaceable, sharpenable, adjustable - 1" thick steel	1 bed knife	4 sided	4 sided	2- pocket, 3/8" chip, 90 FPM (1 knife per pocket)	2-pocket, 3/8" chip, 90FPM
Exhaust Chute	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	360 degree	8" round discharge chute	8" round discharge chute	360 degree manual swivel & adjustable deflector	360 degree manual swivel & adjustable deflector
Hitch	3 point hitch	3 point hitch	Trailer mounted & towable. PTO operated	3 point hitch CAT II	3-point hook up	3-point hook up	3-point hitch	3-point hitch
Options		Speed Sensing	Speed sensing, hydraulic lift cylinder	Specifications not available	Low Profile Discharge Chute Kit	Low Profile Discharge Chute Kit	6-tooth & 21-tooth spline adaptor to connect to PTO shaft, slip clutch for PTO Drive	6-tooth & 21-tooth spline adaptor to connect to PTO shaft, slip clutch for PTO Drive
Dimensions	82" X 83" X 75 1/2"	94" X 61" X 81"	132" X 65" X 91"	52" X 50" X 90"	52" X 47" X 93"	69" X 50" X 93"		
Weight	1350 LBS.	1965 LBS.	3,840 LBS.	1,000 LBS.	885 LBS.	1300 LBS.	2000 - 2200 LBS.	2600 LBS.
Warranty	1 Year	1 Year	1 Year	1 Year	1 year Commercial 2 Years Homeowner	1 year Commercial 2 Years Homeowner	1 Year	1 Year